REDEFINING URBAN MOBILITY

Intencity by Lecapitaine

ELE



Lecapitaine

1

Kangoo

RENAULT Kangoo

High performance insulation, K-value of K 0,37 W/m².°C

Renault Kangoo's compact design, multiple customisation options and driving comfort make it a versatile choice.



Unique design



Simplified maintenance





Technical features

For thermal and **electrical** vehicles 📀

Overall length	Overall height	Wheelbase	Volume	Payload capacity*	Vehicle Gross weigth	Internal length	Internal height	Internal width	Width between wheel arches
L1 model 4 486 mm	Insulated van (without fairing) 1893mm	2 716 mm	1,75 m³	^{up to} 545 kg	^{up to} 2,230 t	1 510		1 320 mm	1 120 mm
				(*) ^{up to} 350 kg	(\$) up to 2,220 t	1 510 mm	1 010 mm		
L2 model 4 910 mm	refrigerated van (with fairing**) 1 975 mm	3100 mm	2,30 m³	^{up to} 555 kg	^{up to} 2,320 t	1 914 mm	1010 11111		
				(4) up to 560 kg	(*) ^{up to} 2,510 t				

* Depending on vehicle's configuration

** Refrigerated unit fairing is optional

Available configurations



Marketing & communication Lecapitaine - FP-40-EN-LC-A

Adjustable shelving

Easy to install, they allow you to organize your deliveries. Need more space? Lift them to optimize the loading area.

Removable plate

This layout allows you to cleverly store your products to optimize your deliveries.

Load restraint tracks

Secure your goods and deliveries with our load restraint tracks. Configure their placement to suit your needs.

Reinforced lock

Because the security of your goods is a priority, the reinforced lock gives you peace of mind in all circumstances.

Other options are available. For more information, contact the sales department via the QR code below.



Parc d'Activités Neptune 1 | 315 rue Louise Michel | 50 009 Saint-Lô CEDEX | +33 (0)2 33 77 85 50 | info@lecapitaine.fr | lecapitaine.com

