

# ntencity

by Lecapitaine



High performance insulation, K-value 0,35 W/m<sup>2</sup>.°C



Unique design



Simplified maintenance



Wide range of option



## **Technical features**

For thermal and **electrical** vehicles (4)



Overall length	Overall height	Wheelbase	Volume	Payload capacity*	Vehicle gross weight	Internal length	Internal height	Internal width	Width between wheel arches
L1 model 4 999 mm	Insulated van (without fairing) 1 893 mm	3 098 mm	3,65 m³	<sup>up to</sup> 795 kg	up to 2,990 t	2 170 mm			
L2 model 5 399 mm	refrigerated van (with fairing**) 2 053 mm	3 498 mm	4,35 m³	up to 825 kg	up to 3,070 t	2 570 mm	1 065 mm	1 480 mm	1 212 mm

- \* Depending on vehicle's configuration
- \*\* Refrigerated unit fairing is optional

# **Available configurations**



### Adjustable shelving

Easy to install, they allow you to organize your deliveries. Need more space? Lift them to optimize the loading area.

### Removable plate

This layout allows you to cleverly store your products to optimize your deliveries.

### **Load restraint tracks**

Secure your goods and deliveries with our load restraint tracks. Configure their placement to suit your needs.

### Strip curtains

To preserve the freshness of your products, the PVC strip curtain reduces temperature loss while allowing easy access to your goods.

Other options are available. For more information, contact the sales department via the QR code below.



Scan this QR code and ask for a quote